

### Mounting angles for 482.6 mm (19")



For front installation of subracks and blanking plates.

**Material:**  
Extruded aluminum section, clear-chromated

**Supply includes:**  
Assembly parts.

**Note:**  
1 pack of threaded inserts and 2 packs of mounting rails and spacers are required for depth-adjustable installation.

For enclosure height	Packs of	Order No. RC
1 U	2	3751.650
2 U	2	3751.660
3 U	2	3751.670
4 U	2	3751.680
6 U	2	3751.690
7 U	2	3751.640
9 U	2	3751.780
12 U	2	3751.790

#### ! Also required:

Threaded inserts, see page 82.  
Mounting rails, see page 82.  
Spacers, see page 82.

### Threaded inserts



#### With M4 thread for RiCase

For the installation of mounting angles, slide rails, mounting kits, cable ducts etc. Simply slide into the channels in the side panels.

**Material:**  
Extruded aluminum section, clear-chromated

For enclosure height	Packs of	Order No. RC
1 U	8	3751.700
2 U	8	3751.710
3 U	8	3751.720
4 U	8	3751.730
6 U	8	3751.740
7 U	8	3751.750
9 U	8	3751.760
12 U	8	3751.770

### Mounting rails



- For depth-variable installation of mounting angles
- For the installation of component shelves, static or pull-out


**Material:**  
Aluminum, clear-chromated

**Supply includes:**  
Assembly parts.

For enclosure depth mm	Packs of	Order No. RC
300	2	3751.400
420	2	3751.410
540	2	3751.420

#### ! Also required:

Threaded inserts, see page 82  
Spacers, see page 82



- A** Version for depth-variable mounting angles
- B** Component shelf installation for 482.6 mm (19") (width 409 mm, also with telescopic slides)
- C** Direct component shelf installation (width 471 mm)

- 1** Threaded inserts
- 2** Short spacers
- 3** Long spacers
- 4** Mounting rails

### Spacers



For the attachment of mounting rails.

Design	Packs of	Order No. RC
Short for depth-variable mounting bracket	4	3751.450
Long for component shelf installation (width 409 mm)	4	3751.460